

View Online at <https://aerobasegroup.com/nsn/4720-01-346-4690>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.371 inches

Temperature Rating:

-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

0.710 inches

Minimum Inside Bending Radius:

5.750 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.719 inches 1st end

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Acid resistant and alcohol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.000 inches

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene; end fitting titanium per ams 4965

Thread Series Designator:

Unjs 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0