## NSN 4720-01-346-4696



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-346-4696 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.560 inches **Minimum Inside Bending Radius:** 2.250 inches **Connection Style:** Swivel nut with compression sleeve 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer braided steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle: 30.0 degrees 2nd end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

11.500 inches

**Thread Series Designator:** 

Unjf 1st end

## NSN 4720-01-346-4696

Nonmetallic Hose Assembly - Page 2 of 2



	<b>L</b> -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0