

View Online at <https://aerobasegroup.com/nsn/4720-01-346-9761>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

**Outside Diameter:**

1.590 inches

**Minimum Inside Bending Radius:**

7.380 inches

**Angle Between Rigid Elbow Fittings In Deg:**

130.0

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

1.312 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Heat resistant and hydraulic solution resistant and fuel resistant and oil resistant and ethylene glycol resistant and solvent resistant and oxidation resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

29.000 inches

**Thread Series Designator:**

Un 2nd end

**Specification Data:**

81349-mil-h-25579 government specification

**Specification Or Standard:**

16 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-25579 spec.