## NSN 4720-01-346-9763

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-346-9763

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.250 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 0.590 inches   |
| Minimum Inside Bending Radius:   |
| 4.000 inches   |
| End Application:   |
| 3930-01-305-2111   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 20000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 5000.0 pounds per square inch  |
| Thread Size:   |
| 0.562 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Outer Covering Environmental Protection:   |
| Abrasion resistant and oil resistant and weatherproof  |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 129.000 inches   |
| Media For Which Designed:  |
| Fuel/oil, hydrocarbon single response  |

Unf 1st end

**Thread Series Designator:** 

## NSN 4720-01-346-9763

Nonmetallic Hose Assembly - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0