

View Online at <https://aerobasegroup.com/nsn/4720-01-347-2791>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.812 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

2.219 inches

Minimum Inside Bending Radius:

13.250 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided steel wire and 2nd layer braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

350.0 pounds per square inch

Thread Size:

2.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

700.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

66.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Specification Data:

96906-ms28741 government specification

Specification Or Standard:

32 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0