Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-347-8482

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.710 inches
Minimum Inside Bending Radius:
5.750 inches
Connection Style:
Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
4000.0 pounds per square inch Thread Size:
0.719 inches 1st end
Seat Angle:
8.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch Inside Surface Condition:
Smooth
Measuring Method And Length:
15.250 inches working
Thread Series Designator: Un 1st end
Specification Data:
76823-07a287 manufacturers standard

NSN 4720-01-347-8482

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

