## NSN 4720-01-347-8483

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Uns 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-347-8483

3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.391 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response				
Outside Diameter:				
0.710 inches				
Minimum Inside Bending Radius:				
5.750 inches				
Connection Style:				
Swivel nut, inverted flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
18 1st end				
Burst Test Pressure:				
16000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
4000.0 pounds per square inch				
Thread Size:				
0.844 inches 2nd end				
Seat Angle:				
8.0 degrees 1st end				
Hydrostatic Test Pressure:				
8000.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
23.500 inches working				
Thread Series Designator:				

## NSN 4720-01-347-8483

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

76823-07a287 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0