NSN 4720-01-348-1498

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-348-1498 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.212 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.470 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut, inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Nuts drilled for lockwire Thready Qty Per Inch (tpi): 24 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 4000.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 8.5 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.125 inches **Thread Series Designator:**

N/a

Unj 2nd end Shelf Life:

NSN 4720-01-348-1498

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0