NSN 4720-01-348-1510

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-01-348-1510 | | | |
|---|--|--|--|
| Cross Sectional Shape: | | | |
| Round | | | |
| Thread Class: | | | |
| 3b 1st end | | | |
| Thread Direction: | | | |
| Right-hand 1st end | | | |
| Inside Diameter: | | | |
| 0.851 inches | | | |
| Tempurature Rating: | | | |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response | | | |
| Outside Diameter: | | | |
| 1.424 inches | | | |
| Minimum Inside Bending Radius: | | | |
| 7.380 inches | | | |
| End Application: | | | |
| Grumman f-14a aircraft | | | |
| Connection Style: | | | |
| Swivel nut flare 2nd end | | | |
| End Connection Design: | | | |
| Straight 1st end | | | |
| Connection Type: | | | |
| Threaded internal tube 1st end | | | |
| Features Provided: | | | |
| Nuts drilled for lockwire | | | |
| Burst Test Pressure: | | | |
| 12000.0 pounds per square inch | | | |
| Layer Composition And Location: | | | |
| Outer layer braided corrosion resistant steel wire | | | |
| Maximum Operating Pressure: | | | |
| 1500.0 pounds per square inch | | | |
| Thread Size: | | | |
| 1.315 inches 1st end | | | |
| Seat Angle: | | | |
| 37.0 degrees 2nd end | | | |
| Hydrostatic Test Pressure: | | | |
| 3000.0 pounds per square inch | | | |

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.500 inches

NSN 4720-01-348-1510

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Design | nator: |
|--------|--------|--------|--------|
| | 0000 | -00.9. | |

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0