NSN 4720-01-348-1511

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.851 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-348-1511

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response				
Outside Diameter:				
1.424 inches				
Minimum Inside Bending Radius:				
7.380 inches				
End Application:				
Grumman f-14a aircraft				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Nuts drilled for lockwire				
Burst Test Pressure:				
12000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
1.312 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
18.500 inches				

NSN 4720-01-348-1511

Nonmetallic Hose Assembly - Page 2 of 2



Thre	ead	Series	Design	nator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0