NSN 4720-01-348-6309

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-348-6309

| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
|---|
| Outside Diameter: |
| 0.490 inches |
| Minimum Inside Bending Radius: |
| 1.500 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 0.025 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Elbow 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability and reusable end fittings |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Flow Angle: |
| 45.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Heat resistant and fuel resistant and oil resistant and solvent resistant and vibration resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 14.875 inches |
| |
| |

NSN 4720-01-348-6309

Nonmetallic Hose Assembly - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

Conductive hose

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0