## NSN 4720-01-348-6312

Nonmetallic Hose Assembly - Page 1 of 2

81343-as621 professional/industrial association standard



View Online at https://aerobasegroup.com/nsn/4720-01-348-6312

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.236 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.420 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant and heat resistant and vibration
resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.000 inches
Thread Series Designator:
Unjf 1st end
Specification Data:

## NSN 4720-01-348-6312

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0