NSN 4720-01-349-3893

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-349-3893

-65.0 degrees fahrenheit single response					
Outside Diameter:					
0.938 inches					
Minimum Inside Bending Radius:					
4.500 inches					
Connection Style:					
Swivel nut, flareless 2nd end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
12 2nd end					
Burst Test Pressure:					
800.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
200.0 pounds per square inch					
Thread Size:					
1.062 inches 2nd end					
Seat Angle:					
12.0 degrees 2nd end					
Hydrostatic Test Pressure:					
400.0 pounds per square inch					
Flow Angle:					
45.0 degrees 2nd end					
Outer Covering Environmental Protection:					
Corrosion resistant and oil resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
23.000 inches					

NSN 4720-01-349-3893

Nonmetallic Hose Assembly - Page 2 of 2



Th	road	Series	Docin	nator:
ιn	reau	Series	Desig	mator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0