NSN 4720-01-349-3898

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-349-3898 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.498 inches **Minimum Inside Bending Radius:** 1.250 inches **End Application:** 4610-01-219-8707 **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 11000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded polyurethane **Maximum Operating Pressure:** 2750.0 pounds per square inch **Thread Size:** 0.250 inches 1st end **Hydrostatic Test Pressure:** 5500.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 72.000 inches **Special Features:** Cover is pin-pricked **Thread Series Designator:** Npt 1st end

Shelf Life:

N/a

NSN 4720-01-349-3898

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0