

View Online at <https://aerobasegroup.com/nsn/4720-01-349-7783>

Cross Sectional Shape:

Round

Inside Diameter:

2.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Flange Thickness:

0.392 inches 1st end

Outside Diameter:

2.297 inches

Minimum Inside Bending Radius:

20.000 inches

Flange Outside Diameter:

3.240 inches 1st end

Connection Style:

Raised 1st end

Raised Face Height:

0.330 inches 1st end

Raised Face Diameter:

2.500 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

Raised face flange 1st end

Features Provided:

Reusable end fittings

Second End Relationship With First End:

Identical

Burst Test Pressure:

4000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided textile yarn err-100

Maximum Operating Pressure:

1000.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

55.500 inches working

Flange Style:

Round w/ out bolt holes 1st end

Special Features:

Assembly is two hose assemblies connected by a 90.0 elbow, fc9528-40-40-188; first and second leg lengths are identical 27.750 inches long; each end connection includes a split clamp, 900-758-2 and a tailpiece, ff-5001-32

Media For Which Designed:

Fuel/oil, hydrocarbon single response and water, fresh single response and water, salt single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0