

View Online at <https://aerobasegroup.com/nsn/4720-01-352-5982>

Cross Sectional Shape:

Round

Thread Class:

1a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.870 inches

Minimum Inside Bending Radius:

7.000 inches

Hose Or Tubing Specification/std Data:

Sae 100r2, type at-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

2010-01-251-2227

Connection Style:

Swivel, plain 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded external pipe 1st end

Features Provided:

Nonskive

Second End Relationship With First End:

Not identical

Burst Test Pressure:

14000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided steel wire err-100

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

90.000 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Specification Data:

Sae 100r2, type at-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0