NSN 4720-01-352-6018

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-352-6018

Cross Sectional Shape:			
Round			
Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.212 inches			
Tempurature Rating:			
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response			
Outside Diameter:			
0.640 inches			
Minimum Inside Bending Radius:			
1.500 inches			
Connection Style:			
Swivel nut, flareless 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Electrostatic discharge capability			
Burst Test Pressure:			
16000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
3000.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
12.0 degrees 1st end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Outer Covering Environmental Protection:			
Fuel resistant and oil resistant and heat resistant and solvent resistant and vibration resistant			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
10.000 inches			
Thread Series Designator:			
Half dat and			

Unjf 1st end

NSN 4720-01-352-6018

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81343-as1339 professional/industrial association specification

Specification Or Standard:

4 size

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0