## NSN 4720-01-352-6027

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.602 inches

**Tempurature Rating:** 

**Outside Diameter:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-352-6027

1.179 inches
Minimum Inside Bending Radius:
3.880 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant and heat resistant and solvent resistant and vibration resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.000 inches

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

## NSN 4720-01-352-6027

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unj 1st end
Specification Data:
81343-as1339 professional/industrial association specification
Specification Or Standard:
12 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0