NSN 4720-01-352-6031

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-352-6031

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.500 inches
Minimum Inside Bending Radius:
12.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
5000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

13.250 inches

NSN 4720-01-352-6031

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designe	d	ľ
-------------------------	---	---

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0