NSN 4720-01-352-9029

Nonmetallic Hose Assembly - Page 1 of 2

81343-as115 professional/industrial association standard



View Online at https://aerobasegroup.com/nsn/4720-01-352-9029

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.406 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response					
Outside Diameter:					
0.615 inches					
Minimum Inside Bending Radius:					
2.875 inches					
Connection Style:					
Swivel nut, flareless 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Burst Test Pressure:					
14000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
3000.0 pounds per square inch					
Thread Size:					
0.750 inches 1st end					
Seat Angle:					
12.0 degrees 1st end					
Hydrostatic Test Pressure:					
6000.0 pounds per square inch					
Outer Covering Environmental Protection:					
Acid resistant and alcohol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
24.500 inches working					
Thread Series Designator:					
Unjf 1st end					
Specification Data:					

NSN 4720-01-352-9029

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0