## NSN 4720-01-353-0512

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-353-0512

Inside Diameter:
0.625 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
1.220 inches
Minimum Inside Bending Radius:
6.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.500 inches
Thread Series Designator:
Un 1st end
Specification Data:
81349-mil-h-25579 government specification

## NSN 4720-01-353-0512

Nonmetallic Hose Assembly - Page 2 of 2



Specification Or Standard:
12 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0

Mil-std (military Standard):

Mil-h-25579 spec.