## NSN 4720-01-353-0514

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-353-0514

0.188 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response					
Outside Diameter:					
0.343 inches					
Minimum Inside Bending Radius:					
2.000 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Features Provided:					
Reusable end fittings					
Burst Test Pressure:					
7000.0 pounds per square inch					
Layer Composition And Location:					
Outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
1500.0 pounds per square inch					
Thread Size:					
0.438 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
3500.0 pounds per square inch					
Outer Covering Environmental Protection:					
Corrosion resistant					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
6.875 inches					
Thread Series Designator:					
Unf 1st end					

## NSN 4720-01-353-0514

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0