Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-353-2920

Cre	oss Sectional Shape:
	und
	read Class:
	1st end
	read Direction:
	ht-hand 1st end
-	ide Diameter:
	25 inches
	npurature Rating:
	.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
	tside Diameter:
	13 inches
Mir	nimum Inside Bending Radius:
	03 inches
	nnection Style:
	ivel nut, flareless 2nd end
	d Connection Design:
	aight 1st end
	nnection Type:
Thr	readed internal tube 1st end
Th	ready Qty Per Inch (tpi):
12	2nd end
Bu	rst Test Pressure:
800	0.0 pounds per square inch
Lay	ver Composition And Location:
Ou	ter layer braided corrosion resistant steel wire
Ма	ximum Operating Pressure:
200	0.0 pounds per square inch
Th	read Size:
1.0	62 inches 2nd end
Sea	at Angle:
12.	0 degrees 2nd end
Hy	drostatic Test Pressure:
400).0 pounds per square inch
Flo	w Angle:
45.	0 degrees 2nd end
Ins	ide Surface Condition:
Sm	ooth
Me	asuring Method And Length:
22.	500 inches working
Th	read Series Designator:
Unj	2nd end

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

76823-07a271 manufacturers standard and 76823-07a224 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0