NSN 4720-01-353-2926

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-353-2926

Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.625 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response				
Outside Diameter:				
0.813 inches				
Minimum Inside Bending Radius:				
7.703 inches				
Connection Style:				
Swivel nut, flareless 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Thready Qty Per Inch (tpi):				
12 2nd end				
Burst Test Pressure:				
800.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
200.0 pounds per square inch				
Thread Size:				
1.062 inches 2nd end				
Seat Angle:				
12.0 degrees 2nd end				
Hydrostatic Test Pressure:				
400.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
31.625 inches working				
Thread Series Designator:				
Unj 2nd end				

NSN 4720-01-353-2926

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

76823-07a271 manufacturers standard and 76823-07a224 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0