

View Online at <https://aerobasegroup.com/nsn/4720-01-353-2927>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

0.813 inches

**Minimum Inside Bending Radius:**

7.703 inches

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

800.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

1.062 inches 2nd end

**Seat Angle:**

12.0 degrees 2nd end

**Hydrostatic Test Pressure:**

400.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.875 inches

**Thread Series Designator:**

Unj 2nd end

**Specification Data:**

76823-07a271 manufacturers standard and 76823-07a224 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0