Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-353-4758

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: 004ter layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Straidet Test Pressure: 200.0 pounds per square inch Hydrostatic Test Pressure: 1.062 inches 2nd end Straidet Size 1.062 inches 2nd end Hydrostatit Test P		
Thread Class: 3b Ist end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -6.5.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Minimum Inside Bending Radius: 7.703 inches Connection Design: Straight 2nd end End Connection Design: Straight 2nd end Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qy Per Inch (tp): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Layer Composition And Location: 1.062 inches 2nd end Maximum Operating Pressure: 1.062 inches 2nd end Murding Eressure: 1.062 inchessure: 1.062 inchessure: 1.062 inchessure: 1.062 inchessure: 1.0		
3) ist end Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: 65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Thready QI Per Inch (tp): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 10.02 jounds per square inch Experimental Thread Steel 10.02 jounds per square inch Experimental Steel 10.02 jounds per square inch Experimental Steel 10.02 jounds per square inch Hydrostatic Test Pressure: 10.02 degrees 2nd end Hydrostatic Test Pressure: 10.00 degrees 1st end Experimenal	Round	
Thread Direction: Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Thread di internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Sett Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 20.0 pounds per square inch Hydrostatic Test Pressure: 20.0 pounds per square inch Hydrostatic Test Pressure: 20.0 degrees 2nd end Hydrostatic Test Pressure: 20.0 degrees 1st end Hydrostatic Test Pressure: Smoth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Thread Class:	
Right-hand 1st end Inside Diameter: 0.625 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 20.0 pounds per square inch Exter Size: 1.062 inches 2nd end Straight 2nd end Microstitic Test Pressure: 1.0 degrees 2nd end Hydrostatic Test Pressure: 0.0 degrees 2nd end Hydrostatic Test Pressure: 10.0 degrees 1st end Strokatic Test Pressure: 10.0 degrees 1st end Hydrostatic Test Pressure:<	3b 1st end	
Inside Diameter: 0.625 inches 0	Thread Direction:	
No.825 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 20.0.0 pounds per square inch Extend Maximum Operating Pressure: 20.0.0 pounds per square inch Hered Size: 1.062 inches 2nd end Mydrostatic Test Pressure: 20.0.0 pounds per square inch Flor Angle: 10.0 egrees 2nd end Mydrostatic Test Pressure: 20.0.0 pounds per square inch Flow Angle: 10.0 egrees 1st end Inside Surface Condition: Smooth <	Right-hand 1st end	
Tempurture Rating: -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Oty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Set Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 10.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 10.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 10.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Angle: 10.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches: working Thread Series Designator:	Inside Diameter:	
-6.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Oty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flew Angle: 10.02 operees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flew Angle: 10.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 1.7.875 inches working <td>0.625 inches</td> <td></td>	0.625 inches	
Outside Diameter: 0.813 inches Minimum Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 1.7.875 inches working Thread Stries Designator:	Tempurature Rating:	
0.813 inches Minimum Inside Bending Radius: 7.703 inches 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Steat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Steat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 1.7.875 inches working Thread Series Designator:	-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response	
Minimu Inside Bending Radius: 7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Thready Oty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Set Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 1.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 1.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 1.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 1.062 inches 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Fired Size: 1.7.875 inches working Thread Size: 7.875 inches working 7.875 inches working	Outside Diameter:	
7.703 inches Connection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Hydrostatic Test Pressure: 90.0 degrees 1st end Flow Angle: 90.0 degrees 1st end Hydrostatic Condition: Smooth Measuring Method And Length: 1.7.875 inches working	0.813 inches	
Conection Style: Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Minimum Inside Bending Radius:	
Swivel nut, flareless 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 90.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Smooth Maxima Contaiton: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	7.703 inches	
End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Connection Style:	
Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Hydrostatic Test Pressure: 90.0 degrees 1st end Hside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Swivel nut, flareless 1st end	
Conection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 1.062 inches 2nd end Seat Angle: 1.062 opunds per square inch Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 1.7.875 inches working Thread Series Designator:	End Connection Design:	
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Straight 2nd end	
Thready Qty Per Inch (tpi):12 2nd endBurst Test Pressure:800.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.062 inches 2nd endSeat Angle:12.0 degrees 2nd endHydrostatic Test Pressure:400.0 pounds per square inchFlow Angle:90.0 degrees 1st endSmothMeasuring Method And Length:17.875 inches workingThread Size:17.875 inches working	Connection Type:	
12 2nd end Burst Test Pressure: 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 1.062 inches 2nd end Seat Angle: 1.000 pounds per square inch Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working	Threaded internal tube 1st end	
Burst Test Pressure:800.0 pounds per square inchLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.062 inches 2nd endSeat Angle:12.0 degrees 2nd endHydrostatic Test Pressure:400.0 pounds per square inchFlow Angle:90.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:17.875 inches workingThread Series Designator:	Thready Qty Per Inch (tpi):	
 800.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator: 	12 2nd end	
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.062 inches 2nd endSeat Angle:12.0 degrees 2nd endHydrostatic Test Pressure:400.0 pounds per square inchFlow Angle:90.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:17.875 inches workingThread Series Designator:	Burst Test Pressure:	
Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:200.0 pounds per square inchThread Size:1.062 inches 2nd endSeat Angle:12.0 degrees 2nd endHydrostatic Test Pressure:400.0 pounds per square inchFlow Angle:90.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:17.875 inches workingThread Series Designator:	800.0 pounds per square inch	
Maximum Operating Pressure:200.0 pounds per square inchThread Size:1.062 inches 2nd endSeat Angle:12.0 degrees 2nd endHydrostatic Test Pressure:400.0 pounds per square inchFlow Angle:90.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:17.875 inches workingThread Series Designator:	Layer Composition And Location:	
200.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Outer layer braided corrosion resistant steel wire	
Thread Size: 1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Maximum Operating Pressure:	
1.062 inches 2nd end Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	200.0 pounds per square inch	
Seat Angle: 12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Thread Size:	
12.0 degrees 2nd end Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	1.062 inches 2nd end	
Hydrostatic Test Pressure: 400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Seat Angle:	
400.0 pounds per square inch Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	12.0 degrees 2nd end	
Flow Angle: 90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Hydrostatic Test Pressure:	
90.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	400.0 pounds per square inch	
Inside Surface Condition: Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	Flow Angle:	
Smooth Measuring Method And Length: 17.875 inches working Thread Series Designator:	90.0 degrees 1st end	
Measuring Method And Length: 17.875 inches working Thread Series Designator:	Inside Surface Condition:	
17.875 inches working Thread Series Designator:	Smooth	
17.875 inches working Thread Series Designator:	Measuring Method And Length:	
Thread Series Designator:		
-	-	
	Unj 2nd end	

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data:

76823-07a271 manufacturers standard and 76823-07a224 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0