## NSN 4720-01-354-0348

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-354-0348

Inside Diameter:
0.625 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.813 inches
Minimum Inside Bending Radius:
7.700 inches
Angle Between Rigid Elbow Fittings In Deg:
105.0
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
1.062 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
21.000 inches

## NSN 4720-01-354-0348

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Hose is conductive

**Thread Series Designator:** 

Unj 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0