## NSN 4720-01-355-0477

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-355-0477

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.620 inches  |
| Minimum Inside Bending Radius:  |
| 2.500 inches  |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Features Provided:  |
| Reusable end fittings   |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:                                       |
| 1st layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.562 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 35.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                 |
| Thread Series Designator:   |
| Unf 1st end   |

## NSN 4720-01-355-0477

Nonmetallic Hose Assembly - Page 2 of 2



| _ |     |      |   |        |  |
|---|-----|------|---|--------|--|
| c | hο  | JIF. |   | .ife:  |  |
| J | 116 |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0