

View Online at <https://aerobasegroup.com/nsn/4720-01-355-5918>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.298 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.475 inches

Minimum Inside Bending Radius:

2.500 inches

End Application:

Lockheed corporation fy88ang tanker

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant and heat resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.000 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as115 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0