## NSN 4720-01-355-5923

Crimped fittings

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-355-5923

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.280 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.470 inches
Minimum Inside Bending Radius:
0.500 inches
Exterior Color:
Blue
End Application:
Mcdonnell-douglas f-18 aircraft
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
Outer layer braided polyamide cord
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Convoluted
Measuring Method And Length:
115.800 inches
Special Features:

## NSN 4720-01-355-5923

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0