

View Online at <https://aerobasegroup.com/nsn/4720-01-355-5924>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.922 inches

Minimum Inside Bending Radius:

5.500 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

7000.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided corrosion resistant steel wire and 2nd layer braided cotton cord and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

1750.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.000 inches

Media For Which Designed:

Hydraulic fluid and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-8795 spec.