

View Online at <https://aerobasegroup.com/nsn/4720-01-355-7638>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.380 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.690 inches

Minimum Inside Bending Radius:

3.500 inches

Exterior Color:

Blue

Angle Between Rigid Elbow Fittings In Deg:

35.0

End Application:

2350-01-305-0028, howitzer self-propelled

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 2nd end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer rubber composition

Maximum Operating Pressure:

4000.0 pounds per square inch

Thread Size:

0.688 inches 2nd end

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.625 inches working

Special Features:

All hyd. Fluid contact surfaces and associated residual hyd. Fluid shall be in accordance with mil-std-1246, cleanliness level 200.

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0