

View Online at <https://aerobasegroup.com/nsn/4720-01-355-7639>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.380 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Outside Diameter:**

0.690 inches

**Minimum Inside Bending Radius:**

3.500 inches

**Exterior Color:**

Blue

**Angle Between Rigid Elbow Fittings In Deg:**

180.0

**End Application:**

2350-01-305-0028, howitzer, self-propelled.

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

16.000 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and outer layer rubber composition

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**Thread Size:**

0.688 inches 1st end

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.120 inches working

**Special Features:**

All hydraulic fluid contact surfaces and associated residual hyd. Fluid shall be in accordance with mil-std-1246

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0