NSN 4720-01-355-7646

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-355-7646

Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response				
Outside Diameter:				
0.690 inches				
Minimum Inside Bending Radius:				
5.000 inches				
End Application:				
G.H. Tennant co scrubber				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
12000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
3000.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
6000.0 pounds per square inch				
Outer Covering Environmental Protection:				
Oil resistant and ozone resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
14.000 inches				
Media For Which Designed:				
Fuel/oil, hydrocarbon single response				

NSN 4720-01-355-7646

Nonmetallic Hose Assembly - Page 2 of 2



Γh	read	Series	Designator:
	Loud	CCITCS	Designator.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0