

View Online at <https://aerobasegroup.com/nsn/4720-01-355-9016>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.800 inches

Minimum Inside Bending Radius:

5.000 inches

Exterior Color:

Blue

End Application:

HOWI-TZ-ER,-MEDI

Connection Style:

Swivel nut, gasket seal 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 2nd end

Burst Test Pressure:

14000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer wrapped rubber, synthetic

Maximum Operating Pressure:

3500.0 pounds per square inch

Thread Size:

0.812 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

7000.0 pounds per square inch

Outer Covering Environmental Protection:

Fire resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

111.000 inches

Special Features:

Hydraulic fluid in accordance with mil-h-std-1246, cleanliness level 200

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0