

View Online at <https://aerobasegroup.com/nsn/4720-01-356-4553>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.800 inches

**Minimum Inside Bending Radius:**

5.000 inches

**Exterior Color:**

Blue

**End Application:**

HOWI-TZ-ER,-MEDI

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

7000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and outer layer wrapped rubber, synthetic

**Maximum Operating Pressure:**

3500.0 pounds per square inch

**Thread Size:**

0.812 inches 1st end

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fire resistant and fuel resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

56.000 inches

**Special Features:**

Hydraulic fluid in accordance with mil-std-1246, cleanliness level 200

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0