Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-356-4554

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

### **Inside Diameter:**

0.260 inches

#### **Tempurature Rating:**

-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.570 inches

Minimum Inside Bending Radius:

#### 3.000 inches

**Exterior Color:** 

Blue

#### **End Application:**

HOWI-TZ-ER,-MEDI

#### **Connection Style:**

Swivel nut, gasket seal 1st end

### End Connection Design:

Straight 1st end

#### **Connection Type:**

Threaded internal tube 1st end

### **Burst Test Pressure:**

20000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer wrapped rubber, synthetic

### Maximum Operating Pressure:

5000.0 pounds per square inch

#### **Thread Size:**

0.562 inches 1st end

### Hydrostatic Test Pressure:

10000.0 pounds per square inch

### **Outer Covering Environmental Protection:**

Fire resistant and fuel resistant

## Inside Surface Condition:

Smooth

### Measuring Method And Length:

16.000 inches

### **Special Features:**

Hydraulic fluid shall be in accordance with mil-std-1246, cleanliness level 200

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0