

View Online at <https://aerobasegroup.com/nsn/4720-01-356-9813>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.905 inches

Minimum Inside Bending Radius:

2.880 inches

End Application:

Mcdonnell douglas aircraft mdl.Series av-8b

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Heat resistant and fuel resistant and oil resistant and ethylene glycol resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.500 inches

Special Features:

Cres 321 tubing, cond a, 1/2 in.X0.065 wall x length not included in pac

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0