## NSN 4720-01-357-2470

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-2470

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.680 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer wrapped rubber, synthetic
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
86.000 inches excluding end fittings
Special Features:
Each hose must have metal band with drexel part number stamped on it
Media For Which Designed:

Fuel/oil, hydrocarbon single response

## NSN 4720-01-357-2470

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator
Npt 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0