Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-2474

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-55.0 degrees celsius single response and 90.0 degrees celsius single response
Outside Diameter:
0.780 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
40.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer braided steel wire err-100
Maximum Operating Pressure:
20.0 pounds per square inch
Thread Size:
0.5625 inches 1st end
Seat Angle:
45.0 degrees 1st end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 9.200 inches Second End Swivel Action Capability: Included **Special Features:** Inner conveying tube material-rubber Media For Which Designed: Liquid, ingested single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0