## NSN 4720-01-357-3443

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-3443

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-55.0 degrees celsius single response and 90.0 degrees celsius single response
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
40.0 pounds per square inch
First End Swivel Action Capability:
Included
Layer Composition And Location:
Outer layer braided steel wire err-100
Maximum Operating Pressure:
20.0 pounds per square inch
Thread Size:
0.4375 inches 1st end
Seat Angle:
45.0 degrees 1st end
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

13.000 inches working

## NSN 4720-01-357-3443

Nonmetallic Hose Assembly - Page 2 of 2



## Second End Swivel Action Capability: Included Special Features: Inner conveying tube material-rubber Media For Which Designed: Liquid, ingested single response Thread Series Designator: Unjs 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A542a0