NSN 4720-01-357-3446

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-3446

| 3b 1st end |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.735 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded polyurethane and 1st layer braided fiber and 2nd layer braided fiber |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Abrasion resistant and hydraulic solution resistant and oil resistant and weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 96.000 inches |
| Special Features: |
| Two flexible hoses permanently joined |
| Thread Series Designator: |
| Unif 1st end |

NSN 4720-01-357-3446

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | | |
|---|----|----|---|----|---|---|
| C | he | 14 | | iŧ | 0 | • |
| J | | | _ | | ㄷ | - |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0