## NSN 4720-01-357-3447

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-3447

3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.375 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
0.735 inches			
Minimum Inside Bending Radius:			
2.500 inches			
Exterior Color:			
Black			
Connection Style:			
Swivel nut flare 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
16000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane			
Maximum Operating Pressure:			
4000.0 pounds per square inch			
Thread Size:			
0.562 inches 2nd end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
8000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Outer Covering Environmental Protection:			
Abrasion resistant and hydraulic solution resistant and oil resistant and weatherproof			
Inside Surface Condition:			
Smooth			

66.000 inches

**Measuring Method And Length:** 

## NSN 4720-01-357-3447

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	_00.9.	

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0