## NSN 4720-01-357-8727

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-8727

Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.375 inches		
Tempurature Rating:		
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response		
Outside Diameter:		
0.735 inches		
Minimum Inside Bending Radius:		
2.500 inches		
Exterior Color:		
Black		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 2nd end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Perforated outer cover		
Burst Test Pressure:		
10000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided fiber and 2nd layer braided fiber and outer layer molded polyurethane		
Maximum Operating Pressure:		
2500.0 pounds per square inch		
Thread Size:		
0.562 inches 2nd end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
5000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Abrasion resistant and hydraulic solution resistant and oil resistant		

18.000 inches

Smooth

**Inside Surface Condition:** 

**Measuring Method And Length:** 

## NSN 4720-01-357-8727

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:
--------	--------	-------------

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0