Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-9604

С	cross Sectional Shape:
R	lound
Т	hread Class:
3	b 1st end
Т	hread Direction:
R	light-hand 1st end
Ir	nside Diameter:
0	.260 inches
Т	empurature Rating:
-6	65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
0	outside Diameter:
0	.375 inches
N	linimum Inside Bending Radius:
4	.000 inches
E	xterior Color:
Ν	latural
С	connection Style:
S	wivel nut flare 2nd end
Е	nd Connection Design:
S	traight 1st end
С	connection Type:
Т	hreaded internal tube 1st end
В	urst Test Pressure:
8	00.0 pounds per square inch
L	ayer Composition And Location:
С	Outer layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
2	00.0 pounds per square inch
т	hread Size:
0	.563 inches 2nd end
S	eat Angle:
3	7.0 degrees 2nd end
Н	lydrostatic Test Pressure:
4	00.0 pounds per square inch
F	low Angle:
4	5.0 degrees 2nd end
lr	nside Surface Condition:
S	mooth
N	leasuring Method And Length:
1	5.875 inches
т	hread Series Designator:
	Injf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

