Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-357-9606

Cross Sectional Shap	e:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.420 inches	
Tempurature Rating:	
-65.0 degrees fahrenhe	it single response and 275.0 degrees fahrenheit single response
Outside Diameter:	
0.500 inches	
Minimum Inside Bend	ing Radius:
5.200 inches	
Exterior Color:	
Natural	
Connection Style:	
Swivel nut flare 1st end	
End Connection Desig	jn:
Straight 1st end	
Connection Type:	
Threaded internal tube	1st end
Burst Test Pressure:	
800.0 pounds per squar	re inch
Layer Composition Ar	nd Location:
Outer layer braided corr	rosion resistant steel wire
Maximum Operating P	ressure:
200.0 pounds per squar	re inch
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pres	sure:
400.0 pounds per squar	re inch
Inside Surface Condit	ion:
Smooth	
Measuring Method An	d Length:
10.125 inches	
Thread Series Designation	ator:
Unjf 1st end	
.	
Shelf Life:	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0