Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-358-6083

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.365 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.575 inches |
| Minimum Inside Bending Radius: |
| 0.750 inches |
| Exterior Color: |
| Black or blue |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Nuts drilled for lockwire |
| Burst Test Pressure: |
| 900.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided polyamide cord |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 600.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Vacuum In Torr: |
| 50.8 |
| Inside Surface Condition: |
| Convoluted |
| |



Measuring Method And Length:

9.290 inches

Special Features:

Crimped fittings

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0