NSN 4720-01-358-6085

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-358-6085

0.370 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.560 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Blue
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nuts drilled for lockwire
Burst Test Pressure:
900.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.563 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Fire resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth

NSN 4720-01-358-6085

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

12.040 inches

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A542a0