NSN 4720-01-358-6086

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-358-6086

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.370 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response				
Outside Diameter:				
0.560 inches				
Minimum Inside Bending Radius:				
0.750 inches				
Exterior Color:				
Blue				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
900.0 pounds per square inch				
Maximum Operating Pressure:				
300.0 pounds per square inch				
Thread Size:				
0.563 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
600.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Fire resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
12.660 inches				
Supplementary Features:				
This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained				

asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

NSN 4720-01-358-6086

Nonmetallic Hose Assembly - Page 2 of 2



		•		
Ιh	read	Series	Desiar	າator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0