## NSN 4720-01-358-6087

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4/20-01-358-608/
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.370 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.560 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Blue
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
900.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.563 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Fire resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.280 inches
Supplementary Features:
This item has been reviewed for asbestos material; the current approved sources, 00624 have indicated their part number contained

asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984

## NSN 4720-01-358-6087

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designa	tor:
-----------------------	------

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0